



HARD WAX OIL

HARD WEARING, WATER & STAIN RESISTANT FINISH

A WATER BASED, NON-FLAMMABLE OIL TO BRING OUT THE NATURAL BEAUTY OF WOOD SURFACES.



Hard Wax Oil is a water based, non-flammable oil which has a low odour when applying. Milky white whilst liquid, it will dry to a hard transparent satin finish.

SPREADING RATE

- 20-30m²/litre depending on the nature and absorbency of the wood.

DRYING TIME

- Touch dry: 30 minutes
- Fully dry & recoating time: 2 hours

TYPE

- Water based and quick drying
- A blend of castor oil, that dries to a hard, durable transparent finish, resistant to stains, alcohol and water.

COLOUR RANGE

- Clear, satin finish

PERFORMANCE ADVANTAGES

- For interior use on wood floors & furniture
- Excellent coverage
- Clear satin natural finish
- Attractive, durable finish
- Low odour
- Non-yellowing on ageing
- Quick Drying
- Generally, has very little effect on the colour of the timber it is applied to

USES

- Interior use only
- Bare wood, hardboard, MDF, unsealed cork, concrete, stone, unsealed quarry and terracotta tiles.

SIZES

- 1 Litre

SHELF LIFE

- Many years if stored in original, tightly closed container in a cool, dry, dark place.

APPLICATION TEMPERATURE

- Ideally between 15°C-25°C
- Do not apply below 10°C

0161 850 0379 | info@polarcoatings.co.uk | polarcoatings.co.uk

Unit 7/8 King Street Trading Estate | Middlewich | Cheshire | CW10 9LF

PREPARATION

- The wood must be bare or sanded clean of any previous coatings.
- The surface must be clean, smooth, dry and free from wax, dust and contaminants.
- Remove any waxes present with a surface cleaner and a scouring pad.
- Wipe off residue with clean rags.
- Oily timbers such as Teak or Iroko must be wiped over with white spirit to remove surface oils which may inhibit drying and penetration of oil.
- Nail holes or narrow gaps may be filled.
- Do not use knotting.

APPLICATION

- Stir well before use.
- Use a brush, sponge or roller. Apply evenly in the direction of grain.
- Leave for a few minutes, then remove excess pools of material using a sponge or rag, spreading any excess oil evenly over the surrounding area.
- **Note:** *Hard Wax Oil may darken some woods, therefore coating a test area first is advised for compatibility.*
- Test before proceeding if other brands of wood colourant are to be used.

COATS

- Apply 3 coats according to the coverage rate.
- More absorbent surfaces or commercial premises may require 4 coats.
- **Important:** *If there is any grain raising after the 1st coat has dried, lightly sand the surface smooth before applying the next coat.*

CLEANING

- Remove as much paint as possible and return to this container.
- Brushes should then be cleaned immediately with water.

MAINTENANCE

- The floor should be vacuumed or swept and then cleaned with a well-wrung cloth or mop, using a mild detergent solution.
- Dirt and scratches may be removed by careful rubbing with a plastic scouring pad.
- If the surface has become dull or worn, it may be revived after cleaning, by re-oiling.

PRECAUTIONS

- Keep out of reach of children.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause respiratory irritation.
- May cause drowsiness or dizziness.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Wash with plenty of water.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Take off contaminated clothing and wash it before reuse.
- EU Limit value for this product (CAT A/f): 130g/l (2010)
- This product contains max 74 g/l VOC

SAFETY

- The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.
- *As Polar Specialist Coatings Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.*
- A Material Safety Data Sheet is available on request.
- *It is the users responsibility to ensure that this data sheet is current prior to using the product.*

0161 850 0379 | info@polarcoatings.co.uk | polarcoatings.co.uk

Unit 7/8 King Street Trading Estate | Middlewich | Cheshire | CW10 9LF